

compustar 2wshlcdr-703 manual

Save this Book to Read compustar 2wshlcdr-703 user manual PDF eBook at our Online Library. Get compustar 2wshlcdr-703 user manual PDF file for free from our online library.



COMPUSTAR 2WSHLCDR 703 USER MANUAL

YYRHFYMEH | PDF | 239.66 KB | 15 Oct. 2013

File Name: compustar 2wshlcdr-703 manual.pdf

Size: 2845 KB

Type: PDF, ePub, eBook

Category: Book

Uploaded: 12 May 2019, 15:48 PM

Rating: 4.6/5 from 665 votes.

Status: AVAILABLE

Last checked: 16 Minutes ago!

In order to read or download compustar 2wshlcdr-703 manual ebook, you need to create a FREE account.

[**Download Now!**](#)

eBook includes PDF, ePub and Kindle version

TABLE OF CONTENT

Introduction
Brief Description
Main Topic
Technical Note
Appendix
Glossary

PDF file compustar 2wshlcdr-703 user manual

Page 1

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with compustar 2wshlcdr-703 manual . To get started finding compustar 2wshlcdr-703 manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



Book Descriptions:

compustar 2wshlcdr-703 manual

Be sure to check that it is the user manual to exactly the device that you are looking for. In our database CompuSTAR 2WSHLCDR703 it belongs to the category Automobile Alarm. A user manual CompuSTAR 2WSHLCDR703 is taken from the manufacturer, a CompuSTAR company it is an official document, so if you have any doubts as to its contents, please contact the manufacturer of the device CompuSTAR 2WSHLCDR703 directly. You can view the user manual CompuSTAR 2WSHLCDR703 directly online or save and store it on your computer. All remotes must be coded at the same time. Following those three flashes the parking lights will The parking lights will flash twice signaling the end The parking lights will flash once All systems except the P2WSSR, can recognize up to three remotes. Contact your dealer or call us directly. If you have any questions, you can ask them in the form below. Other users viewing this website will have the opportunity to help you solve your problem with CompuSTAR 2WSHLCDR703. Remember that you can also share the solution. If you solved the problem yourself, please write the solution to the problem with CompuSTAR 2WSHLCDR703 you will surely help many users by doing so. Ask a question our users can help you. CUATELA Cambios o modificaciones no expresamente aprobadas por la parte responsable del cumplimiento de la norma, pueden anular la autorización del usuario para operar este dispositivo. In order to truly enjoy the benefits of this system, we recommend that you thoroughly review the following manual. This manual also supports your 1 Way Fiance remotes that may be included with your system. No programming is required when replacing the battery. Two Way Remotes First, release the battery cover lock located on the back of the remote. Once the lock is released, gently slide the battery cover off to expose the battery. With the exception of the 2WSSRPRO Uses 1 AA battery all Firstech 2 Way remotes require one AAA battery. httpdocs/pic/file/8051_microcontroller_kit_manual.xml

- **compustar 2wshlcdr-703 manual, compustar 2wshlcdr-703 manual, compustar 2wshlcdr-703 manual pdf, compustar 2wshlcdr-703 manual download, compustar 2wshlcdr-703 manual free, compustar 2wshlcdr-703 manuals.**

While armed, the system will monitor the doors, trunk, hood, shock sensor, and aux inputs. Page 8 Impact This icon will be displayed if an impact to the vehicle is detected while the system is armed. The remote will beep rapidly while displaying this icon if the impact is hard; this means that the alarm was triggered. If it beeps slowly while displaying this icon, that means that the impact was soft and that the alarm simply gave four warning chirps. Door This icon will be displayed if the door is opened while the system is armed. The remote will beep rapidly while displaying this icon. Page 9 General System Functions The remote transmitter functions have been predetermined and programmed from the factory. Sending Commands When in range, and a command has been sent, the remote pager backlight will illuminate, the remote will beep and the appropriate icon will be displayed. Reservation Mode must be set each and every time you want to remote start a manual transmission vehicle. The purpose of Reservation Mode is to leave the transmission in neutral before exiting the vehicle. IMPORTANT The transmission must be left in the neutral position. The vehicles windows must be rolled up. These outputs can be configured for pulsed, timed or latched settings. Your authorized Firstech dealer can set these outputs up accordingly. The remote will beep twice and the shock sensor icon will illuminate to confirm the shock sensor is off. The remote will beep once and the shock sensor icon will disappear to confirm the shock sensor is on. IMPORTANT Turning off the shock sensor also turns off the optional sensor. The remote will beep once and the 2nd car icon will illuminate to confirm that 2nd car mode is activated. The remote will beep twice

and the icon will disappear to confirm 2nd car mode is off. IMPORTANT 2nd car mode requires the remote to be programmed to a 2nd vehicle that is equipped with the same system. <http://amrithaayurvedhospital.com/userfiles/8051-microcontrollers-hardware-manual.xml>

If you are not using the RPS unlock, following the below procedures to program your secure valet pass code; Timer start mode is used to cool or warm the vehicle automatically without use of the key or the remote. It allows you to configure your timer start feature to check the vehicle's temperature prior to starting. All of these options require programming from your local dealer. Your system has a mode that requires you to keep your remote separate from your key chain. This feature also requires additional labor. All remotes must be coded at the same time. The vehicle's parking lights will flash once with the successful completion of this step. Page 17 Alarm Diagnostic Limited Lifetime Warranty While the alarm is armed, the LED will blink slowly. While the siren is going off, the LED will indicate the specific zone that was triggered. Para disfrutar de verdad los beneficios de este sistema, nosotros recomendamos que usted completamente lea el siguiente manual. Este manual tambien contiene informacion sobre el control remoto de 1 via que pueda ser incluido con su sistema. Page 21 Referencia Rapida Remoto de 2 Vias Primero, abra la cerradura de la tapa de la bateria localizada en la parte trasera del remoto. Una vez abierta, suavemente deslice la tapa de la bateria para exponer la bateria. Con la excepcion del remoto 2WSSRPRO Usa 1 bateria del AA todos los remotos de 2 vias Firstech, requieren de una bateria AAA. IMPORTANTE Este seguro observar la polaridad correcta al instalar la bateria. Mientras armado, el sistema supervisara las puertas, cajuela, cofre, sensor de golpes, y entradas auxiliares. Si cualquiera de estas entradas se activa mientras el sistema se encuentra armado, la alarma se activara. Abrir Cajuela Este icono se desplegara cuando la funcion de liberar cajuela se ha activado. Page 25 Impacto Este icono se desplegara si un impacto al vehiculo se descubre mientras el sistema este armado.

El remoto emitira una senal sonora rapida, mientras despliega este icono, si el impacto es duro; esto significa que la alarma fue activada. Si emite una senal sonora lenta, mientras despliega este icono, significa que el impacto era suave y que la alarma dio cuatro chirridos de advertencia. Puerta Este icono se desplegara si la puerta se abre mientras el sistema se encuentra armado. Page 26 Funciones Generales del Sistema Las funciones del transmisor fueron predeterminadas y se han programado en la fabrica. Enviando Comandos Cuando en rango, y una orden sea enviada, la pantalla del remoto iluminara, el remoto emitira una senal sonora y el icono apropiado se desplegara. El Modo Reservacion debe ponerse cada vez que usted quiera encender su vehiculo de transmision manual a control remoto. El proposito de Modo Reservacion, es dejar la transmision en neutral, antes de salir del vehiculo. IMPORTANTE La transmision debe quedar en la posicion neutral. Estas salidas pueden configurarse para pulso momentaneo, temporizado o fijo. Su distribuidor autorizado Firstech puede preparar estas salidas de acuerdo a sus necesidades. El remoto emitira una senal sonora dos veces y el icono del sensor de golpes iluminara para confirmar que el sensor de golpes esta apagado. El remoto emitira una senal sonora una vez y el icono de sensor de golpes desaparecera para confirmar que el sensor de golpes esta encendido. Page 30 Funciones Avanzadas del Sistema Funciones Avanzadas del Sistema El RPS es una funcion opcional. Page 31 Funciones Avanzadas del Sistema Funciones Avanzadas del Sistema Para programar un tiempo especifico de arranque, utilizado para Opcion 3, realice los siguientes pasos; PASO 1 Encienda Opcion 310III. Opcion programada por el distribuidor El modo de arranque temporizado se utiliza para refrescar o calentar el vehiculo automaticamente, sin necesidad de la llave o el remoto. Mientras activado, el arranque temporizado se activara aunque el remoto este fuera de rango.

Page 32 Funciones Avanzadas del Sistema Funciones Avanzadas del Sistema Su sistema tiene un modo que le permite guardar su remoto separado de las llaves del vehiculo. Esta configuracion requiere mano de obra adicional. Para mas detalles, por favor consulte a su instalador. El modo AntiAsalto le permite desactivar su vehiculo despues de que un ladron se haya marchado con su

propiedad. Si usted es asaltado y todavía tiene su remoto, usted puede presionar el botón IV de pánico durante 4 segundos. Page 34 Diagnostico de Alarma Mientras la alarma este armada, el LED destellara lentamente. Mientras la sirena suena, el LED indicara la zona especifica que se acciono. Please check your inbox, and if you can't find it, check your spam folder to make sure it didn't end up there. Please also check your spam folder. Could have been used and returned. Call the place where you purchased it talk to them. Double check. Wiring diagram for 2017 Dodge Ram to install remote. So just look at the list and choose manual for Compustar Automobile Alarm 2W9000FMR907 VA5JR561FM907 7087AR561F907. Share link. By Firstech, LLC Thank you for purchasing a Firstech system for your vehicle. In order to truly enjoy the benefits of this system, we recommend that you thoroughly review the This manual also supports your 1 Way Fiance remotes that may be included with your system. There are certain There may also be features listed in this manual that require additional installation or If you have any questions, please contact the original place of purchase. For further information you may also contact our Warranty Coverage. Caution The Manufacturer's warranty will be voided if this product is installed by anyone other than an authorized Firstech dealer. For complete warranty details Firstech remotes carry a 1 year warranty from original date of purchase. Warranty registration can be completed online by visiting www.compustar.com. Please complete the registration form within 10 days of purchase.

<http://granit-gabro.com/images/camera-digital-samsung-sl-102-manual.pdf>

We do not To verify that an authorized dealer installed your system, we highly By Firstech, LLC. Quick Reference. When servicing or loaning your vehicle to others, the system should be placed in Valet Mode. Valet Mode prevents the system from remote starting and disables IMPORTANT While in Valet mode the remote will still control power lock and unlock systems. The parking lights will not flash. The system can be put into valet one of three ways Repeat this process to take the system out of valet mode. The parking lights will flash twice and Z's will disappear to confirm the system is out of valet mode. Shortly after the first flash, the parking lights will flash twice. A remote control is required to By Firstech, LLC The only regular maintenance this system requires is remote control battery replacement. Two Way Remotes. First, release the battery cover lock located on the back of the remote. Once the lock is released, gently slide the battery cover off to expose the battery. With the IMPORTANT Be sure to observe correct polarity when installing the battery. One Way Remotes. First, remove the small Phillips screw located on the back of the remote. Once the screw has been removed, gently pull the remote apart taking care to not damage Your battery size should be listed on the battery. Replacements can be purchased from your Quick Reference. Button Adjust the time settings by tapping STEP 2 Non Pro Remotes After entering programming mode tap button I and the time icon will flash to set the time. Adjust the time settings Duration. Additional Programming. Required Run time extender. Resets remote start and turbo run time while vehicle is remote started. Aux 1. Triggers the auxiliary 1 output most commonly used for rear defrost or window rolldown. Activates the remote start. Repeat and remote start will shut off. Aux 2. Triggers the auxiliary 2 output most commonly used for rear defrost or window rolldown. Trunk pop. Triggers the trunk release output and opens the vehicle's trunk.

<http://granit-evolution.com/images/camera-digital-samsung-s730-manual.pdf>

Pro Remotes Only Turns on the CompuGLO backlight Option programming menu 1. For use during installation Valet mode see page 8 for details By Firstech, LLC. By Firstech, LLC Quick Reference. Button. Duration. Required. By Firstech, LLC. Required Drive lock. Activates ignition controlled door locks Option programming menu 2. For use during installation Accesses remote option programming Aux 1. Triggers the auxiliary 1 output most commonly used for rear defrost or window rolldown Activates timer start mode. Timer start mode has multiple programmable settings Trunk release. Triggers the trunk release output and opens the vehicle's trunk. Activates Turbo timer mode. Aux 2. Triggers the auxiliary 2 output most commonly used for rear defrost or window

roll down Activates the 2nd Car function Activates the remote start. Repeat and remote start will shut off
Option programming menu 1 Installers Only Valet mode see Valet Mode section for details
By Firstech, LLC Remote LCD liquid crystal display Diagram and icons. Your remote pager will indicate the status of your vehicle while in range. Required Drive lock. Activates ignition controlled door locks.
Option programming menu 2 Installers Only Activates timer start mode. Timer start mode has multiple programmable settings
Activates the built in Turbo timer function. Additional installation is required when using this. Lock. Status. Shock. Sens off. Turbo. Signal. Strength. Impact. Start. Avail Hood. By Firstech, LLC Ign. Con. Door Locks. Siren. Cold Start. Vibration. Parking. Lights. Engine. Running. Valet. Battery. Volage. Aux. Temperature
If you would like additional information on the functionality of your 1 way companion remote, please visit the support page at www.compustar.com
Trunk. Passive Car Call. Auto. Alarm. Clock Remote LCD liquid crystal display Diagram and icons. Engine Running. This icon will be displayed while the vehicle is running after it has been remote started.

While armed, the system will monitor the doors, If any of these inputs are triggered while the system is armed, the alarm will be triggered. Start Availability. This icon will be displayed when the vehicle is ready to be remote started. If this icon is not displayed, you will not be able to remote start the vehicle. Trunk Release. This icon will be displayed when the trunk release function has been activated. By default, the system will be disarmed and the Timer Mode. This icon will be displayed when Timer mode is active. Timer mode can be set up to start the vehicle every 1.5, 3, or once every 24 hours. Signal Strength. This icon is displayed if the last communication to the vehicle was successful. Valet Mode. This icon will be displayed while you are in Valet mode. While in valet mode, the system will not perform any functions other than
If any other function is attempted, Sleep will be Battery Indicator. This icon displays the remaining battery life left in 25% increments. Car Call. This icon will be displayed while someone is attempting to contact you using the RPS sensor. To trigger the RPS sensor, you must
Something that creates a higher pitch, like a key, is better suited to trigger the RPS. By Firstech, LLC Cold Start mode will start the vehicle if the vehicle reaches a
These temperatures can be adjusted by the installer. This icon will be displayed if the siren is turned on. Turning the siren off only applies to the chirps when arming, disarming, or Hood. This icon will be displayed if the hood is opened while the system is armed. This means that the alarm was triggered. If this icon appears while trying to remote start the vehicle, it means that the vehicle will
This icon will be displayed if an impact to the vehicle is detected while the system is armed. The remote will beep rapidly while
If it beeps slowly while displaying this icon, that Door. This icon will be displayed if the door is opened while the system is armed.

If this icon appears while trying to remote start the vehicle, it means that the vehicle will Trunk. This icon will be displayed if the trunk is opened while the system is armed. If this icon appears while trying to remote start the vehicle, it means that the vehicle will Car Call. Passive Mode. This icon will be displayed if Passive mode is currently active. Passive mode will automatically arm the system 30 seconds after the
This mode is ignored while the ignition is on Drive Lock. This icon will be displayed if Drive Lock mode is currently active. Drive Lock mode will lock the doors automatically if the ignition is
The doors will be unlocked when the ignition is turned off. In a manual transmission vehicle the doors will
By Firstech, LLC This icon will be displayed if Turbo mode is currently active. While Turbo mode is active, the vehicle will remain running for a
This will be displayed while you are in 2nd Car mode. 2nd Car mode allows you to control another vehicle with the same
The remote needs to be coded to the other vehicle in 2nd Car mode for this feature to work. This icon will be displayed if the remote is set to vibrate only. While the remote is set to vibrate only the remote will not beep,
The remote will still vibrate in this mode. Alarm Clock. This icon will be displayed if the Alarm Clock function is turned on. When the clock reaches the preset time, the remote will Press button IV for 0.5 sec. to silence the remote. Shock Sensor Bypassed This icon is always displayed on starter only systems because there is no shock sensor. This icon will be displayed while you are in

Aux mode. During this time, you can activate auxiliary outputs 1 or 2 by pressing Voltage. This icon will be displayed while the remote is reporting the voltage of the vehicle or remote battery. Temperature. This icon will be displayed while the remote is reporting the temperature of the vehicle. The remote transmitter functions have been predetermined and programmed from the factory.

The four button configuration allows for many functions to be. Sending Commands. When in range, and a command has been sent, the remote pager backlight will illuminate, the remote will beep and the appropriate icon will be displayed. For Once the vehicle has successfully remote started, the remote will receive a command Receiving Commands. The remote pager will receive commands indicating the status of the vehicle, confirmation of sending commands and alarm notifications. For example, after. To see if your pager is in If your vehicle is locked, tap button I to unlock; if your vehicle is unlocked, tap You will not be able to start your vehicle with the key. IMPORTANT If the alarm has been triggered Siren is going off, you must wait until the remote pager has been paged before disarming the alarm the first. By Firstech, LLC The system can be configured to passively lock and arm the vehicle. While in passive mode, the system will lock and arm the alarm 30 seconds after the last door is closed. As an indicator that the vehicle is going to passively lock If you want Press button II for 2.5 seconds to remote start an automatic transmission vehicle. If you are in range and if the vehicle is ready to remote start, the If you are in range and the remote beeps three times, there is a remote start error. Refer to the "remote start error diagnostic" on the last page of this Upon receiving confirmation that your vehicle is running, the LCD will flash the exhaust icon and the clock icon will begin to show the The remote start runtime can be programmed for 3, 15, 25 or 45 minutes ask your local CompuStar IMPORTANT Your vehicle's key must be inserted into the ignition and turned to the "on" position prior to driving your vehicle. If the foot brake is PDF Version 1.3. Linearized No. Create Date 20090916 1831180700. Modify Date 20090916 1831180700. Page Count 9. Creation Date 20090917 013118Z. Mod Date 20090917 013118Z. Producer Acrobat Distiller 5.0.5 Windows. Author ltsai.

Metadata Date 20090917 013118Z. Creator ltsai. Title VA5JR703A433 User Manual Part1.PDF.